

BM3VET PRO

Uncompromising Value
8.0" Touch Screen LCD Monitor



The BM3Vet Pro encapsulates over 20 years of our intricate research, development, and design dedicated to serve Animal Health practitioners around the globe. Our core values of functional simplicity, elite performance, and uncompromising value are carefully engineered into what we believe to be the most trusted brand in Veterinary multiparameter monitors on the market today. Because everything we do focuses on the needs and efficiency of the clinic, we include premium data management software (BT-Link and BT-Link Mobile) with all of our monitors at no additional cost.

Superior Advantages

- ▶ ECG, SpO₂, NIBP, Respiration, Temperature
(Option: EtCO₂, Dual Gas, Anesthetic Gas/O₂)
- ▶ 8.0" color TFT touch screen for clear parameter display
- ▶ Individual sweep speed setting for each parameter
- ▶ 168 full hours of trend data are stored
- ▶ Screen freeze ON/OFF
- ▶ Extendible parameters
 - Mainstream/Sidestream EtCO₂
 - Mainstream/Sidestream Anesthetic Gas/O₂
 - Dual Gas (EtCO₂ and anesthetic gas monitoring)

- ▶ Enhanced Data Management & connectivity
 - Easy network connectivity, supports wireless LAN
 - B2B, Up to 4 BM3Vet Pro can be controlled by one of the networked BM Pro Series
 - BT-LINK Pro and BT-LINK Mobile for real-time monitoring and data recording
 - USB memory storage
- ▶ Advanced Cardiac Parameters
 - ST level, PVC count real-time display
 - 3 kinds of arrhythmia analysis
- ▶ Versatile
 - Up to 2hrs for continuous operation
 - External HDMI output for large screen

SPECIFICATIONS

General

| | |
|---------------------------------|--|
| Display, Resolution | 8" wide color touch TFT LCD, 800 x 600 pixels |
| Dimension, Weight | 238 (W) x 250 (H) x 163 (D) mm, approx. 3.1 kg |
| Trace | 4 waveforms : ECG, SpO ₂ , RR or EtCO ₂ or MGAS Sweep speed : 6.25, 12.5, 25, 50 mm/sec |
| Indicators | Categorized alarms (3 priority levels) Visual alarm lamp handle QRS beep & SpO ₂ pulse beep Percent(%) SpO ₂ pitch tone Battery status, external power LED Touch screen, rotary knob |
| Interfaces | Power supply : AC 100-240V(50/60Hz) DC input connector : 18VDC, 2.8A LAN digital output for transferring data Nurse call system connection 0.3A at 125 VAC, 1A at 24 VDC External HDMI monitor connection USB barcode reader USB memory data storage / Software Upgrade |
| Battery | Rechargeable Li-ion battery, 2 hours for continuous operation |
| Thermal Printer (option) | Speed : 25, 50mm/sec, paper width : 58mm |
| Data Storage | 168 hours trends, 20 cases of 10 sec alarm waveform |
| Language | English, French, Spanish, Italian, German, Chinese, Russian, Czech, Polish, Turkish, Romanian, Portuguese Bulgarian, Hungarian, Korean, Japanese, Greek |

Accessory

| | | |
|-----------------------------|--|------|
| Standard Accessories | 3 lead vet ECG cable | 1ea |
| | NIBP extension hose (3m) | 1ea |
| | NIBP vet cuff neonate disposable #1-#5 | 1ea |
| | NIBP vet cuff infant (reusable) | 1ea |
| | SpO ₂ extension cable (2m) | 1ea |
| | Esophageal ECG probe with temperature | 1ea |
| | Extension cable for esophageal probe | 1ea |
| | Transflectance SpO ₂ probe | 1ea |
| | Temperature probe (rectal/esophageal) | 1ea |
| | Reusable multisite SpO ₂ probe | 1ea |
| | DC adapter (18 VDC, 2.5A) | 1set |
| | BT-Link Pro (automated record keeping software) | 1ea |
| Optional Accessories | 5 lead vet ECG cable | |
| | Temperature probe (skin) | |
| | Mainstream EtCO ₂ airway adapter kit | |
| | Sidestream EtCO ₂ airway adapter kit | |
| | ECG alligator clip (5ea) | |
| | 3 lead ECG cable (snap type) | |
| | Dual gas accessories (water Trap, patient sample line/adapter, mount) | |

Optional Module

Mainstream EtCO₂ module (sensor)
Sidestream EtCO₂ module (sensor)
Dual Gas module (sensor)
Anesthetic gas/O₂ module (sensor)

Performance

ECG

| | |
|-----------------------------|--|
| Leads Type | 3-lead, 5-lead(Optional) |
| Lead Selection | 3-lead : I,II,III 5-lead(Optional) : I,II,III, aVR, aVL, aVF, V |
| ECG Waveforms | 3-lead: 1 channel 5-lead(Optional): 1 channel |
| Heart Rate Range | Horse, dog: 30 to 300 BPM, Puppy, cat: 30 to 350 BPM |
| Heart Rate Accuracy | ± 1BPM or ± 1%, whichever is greater |
| Sweep Speed | 6.25, 12.5, 25, 50 mm/sec |
| Filter | · Diagnosis : 0.05 to 150 Hz · Monitoring : 0.5 to 40 Hz · Moderate : 0.5 to 25 Hz · Maximum : 5 to 25 Hz |
| S-T Segment Detection Range | -2.0 to 2.0 mV |
| Arrhythmia Analysis | ASYSTOLE, VTACH, VTAC/V-FIB |
| Protection | Against electrosurgical interference and defibrillation |

Respiration

| | |
|-------------------|----------------------------|
| Method | Thoracic impedance |
| Channel Selection | RA-LA or RA-LL |
| Measurement Range | 5 to 120 breath per minute |
| Accuracy | ±1 breath per minute |
| Apnea Alarm | Yes |

SpO₂

| | |
|---------------------|--|
| Saturation Range | 0 to 100% |
| Saturation Accuracy | 70 to 100% ±2 digits, 0 to 69% unspecified |
| Pulse Rate Range | 30 to 254 BPM |
| Pulse Rate Accuracy | ±2 BPM |

NIBP-Suntech

| | |
|----------------------------|---|
| Method | Oscillometric |
| Operation Mode | Manual / Automatic / Continuous |
| Pressure Range | 0 to 300mmHg (accuracy : ±3mmHg) |
| Measurement Range | Systolic: 40 – 265mmHg, MAP: 27 – 222mmHg, Diastolic: 20 – 200mmHg |
| Initial Inflation Pressure | Large animal mode: 160 mmHg (default), Variable from 120 - 280 mmHg Small animal mode: 160 mmHg (default), Variable from 60 - 280 mmHg |
| Pulse Rate Range | 25 to 300 BPM (Beat Per Minute) |

Temperature

| | |
|-------------------|---------------------------------------|
| Channels | 1 |
| Measurement Range | 0 to 50°C (32 to 122°F) |
| Accuracy | 25 to 50°C: ±0.1°C, 0 to 24°C: ±0.2°C |
| Compatibility | YSI Series 400 temperature probes |

Mainstream EtCO₂, Sidestream EtCO₂ - Respirationics (Option)

| | |
|----------------------|--|
| Measurement Range | 0 to 150 mmHg, 0 to 19% |
| Accuracy | 0-40mmHg ±2mmHg, 41-70mmHg ±5% of reading, 71-100mmHg ±8% of reading, 101-150mmHg ±10% of reading |
| Respiration Rate | 0 to 150 breath per minute (Mainstream EtCO ₂) 2 to 150 breath per minute (Sidestream EtCO ₂) |
| Respiration Accuracy | ±1 breath per minute |

Dual Gas-Bionet (Option)

| | |
|------------------|--|
| Method | Sidestream |
| Gas | CO ₂ , Iso, Sev, Enf, Hal, Des |
| Range, Accuracy | CO ₂ : 0~10%, ± (0.2 vol% + 4% relative) Hal/Iso/Enf /Hal: 0~6%, ± (0.15 vol% + 4% relative) Des : 0~18%, ± (0.15 vol% + 4% relative) |
| Respiratory Rate | 0~150BPM ± 1BPM |

Anesthetic Gas/O₂ - Masimo (Option) (to be provided upon request)

- * Specifications can be changed without prior notification.
- * You may have distortion or signal noise when you use nonstandard or other brand's accessories. We strongly recommend you use only the authorized accessories which we supply.
- * The ST algorithm has been tested for accuracy of the ST segment data. The significance of the ST segment changes need to be determined by a veterinarian.



Bionet America, Inc.
Tel : +1-714-734-1760

www.BionetUS.com
E-mail: sales@BionetUS.com